



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

Brochure AiroClearWall V2000 V90



Energy efficiency class

Selected product

- Article no.: 6203200001
- EAN code: 7630029474310
- Product category: Range hood
- Standard width: 90 cm
- Front design: BlackDesign
- Installation method: Wall hood



Details AiroClearWall V2000 V90

Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

Design

- Product category: Range hood
- Standard width: 90 cm
- Front design: BlackDesign
- Installation method: Wall hood

Dimensions

- Front height: 505.3 mm
- Appliance width: 898 mm
- Appliance depth: 355 mm
- Max. appliance depth: 355 mm
- Declared weight: 19 kg

Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting technology: LED
- Number of light sources: 2

Environmental footprint

- Ecopoints end of life (EP): 856195
- Ecopoints device (EP): 408942
- Carbon footprint end of life (kg CO₂e): 304
- Carbon footprint device (kg CO₂e): 143
- Monetary equivalent end of life (CHF): 370
- Monetary equivalent device (CHF): 212

Energy

- Output - standby off: 0.49 W
- Consumption when off: 0 W
- Energy efficiency class: A
- Annual energy consumption: 47.5 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 34.2
- Fluid dynamic efficiency rating: A
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 2 x 2.5 W
- Frequency (1): 50 Hz
- Connected loads (1): 0.255 kW
- Fuse protection (1): 10 A
- Plug type: Schuko 16A
- Connection cable: 1.5 m

Range hood features

- Grease filter cleaning indicator
- Hood design: Slanting hood
- LED candle: LED spot
- Activated charcoal filter saturation indicator
- Power levels: 3 + i
- Grease filter: 2
- Side exhaust
- EcoStandby
- Non-return flap, integrated/attached: Included

Functions

- Extracted air
- Grease filter cleaning indicator
- Side exhaust
- Recirculation air
- Activated charcoal filter saturation indicator
- Intensive setting
- Automatic after-running time

**Additional data**

- Light colour in kelvin: 3000 K
- Exhaust air connection (diameter): 150 mm
- Lighting efficiency: 76.1
- Illumination on cooking surface: 381 lux
- Grease absorption capacity rating: D
- Extracted air output, intensive setting: 720 m³/h
- Extracted air output, max. setting: 535 m³/h
- Extracted air output, min. setting: 300 m³/h
- Recirculation air output, intensive setting: 475 m³/h
- Recirculation air output, max. setting: 445 m³/h
- Recirculation air output, min. setting: 295 m³/h
- Extracted air noise output, intensive setting: 70 dB(A)
- Extracted air noise level, max. setting: 62 dB(A)
- Extracted air noise output, min. setting: 50 dB(A)
- Recirculation air noise output, intensive setting: 75 dB(A)
- Schalleistung Umluft max. Stufe: 73 dB(A)
- Recirculation air noise output, min. setting: 65 dB(A)
- Motor(s): 1
- Motor output: 250 W