



# Data sheet AiroClearWall V2000 V90

Article no.: 6203200001

Compliant to regulation (EU) Nr. 65/2014, (EU) Nr. 66/2014

Name	Unit	Value
Recirculation air noise output, min. setting	dB(A)	65
Schalleistung Umluft max. Stufe	dB(A)	73
Recirculation air noise output, intensive setting	dB(A)	75
Consumption when off	W	0.0
(EU) Nr. 65/2014		Yes
(EU) Nr. 66/2014		Yes
Product category		Range hood
Annual energy consumption	kWh	47.5
Time increase factor		0.8
Fluid dynamic efficiency		34.2
Fluid dynamic efficiency rating		A
Energy efficiency index		47
Pressure capacity at best efficiency point	Pa	450
Extracted air output, min. setting	m <sup>3</sup> /h	300
Extracted air output, max. setting	m <sup>3</sup> /h	535
Extracted air output, intensive setting	m <sup>3</sup> /h	720
Electric power input at best efficiency point	W	150
Nominal lighting output (quantity x W)		2 x 2.5 W
Illumination on cooking surface	lx	381
Output - standby off	W	0.49
Extracted air noise output, min. setting	dB(A)	50
Extracted air noise level, max. setting	dB(A)	62
Extracted air noise output, intensive setting	dB(A)	70
Grease absorption capacity		65.1
Grease absorption capacity rating		D
Lighting efficiency		76.1



Lighting efficiency rating

A

---